



DM

Lightweight Click Wrench (Adjustable)



Single or double square drive models.

| Model | Item # | Square Drive | Torque Ranges | | Graduation | |
|-----------|--------|--------------|--------------------|-----------------|------------|--------|
| | | | American | S.I. | American | S.I. |
| DM 12 | 110101 | Single | 10 - 100 lbf.in | 1 - 12 N.m | 10 lbf.in | 1 N.m |
| DM 30 | 110115 | Single | 50 - 270 lbf.in | 6 - 30 N.m | 10 lbf.in | 1 N.m |
| DM 30-D | 110121 | Double | 50 - 270 lbf.in | 6 - 30 N.m | 10 lbf.in | 1 N.m |
| DM 40 | 110102 | Single | 70 - 350 lbf.in | 8 - 40 N.m | 50 lbf.in | 5 N.m |
| DM 40-D | 110122 | Double | 70 - 350 lbf.in | 8 - 40 N.m | 50 lbf.in | 5 N.m |
| DM 120 | 110103 | Single | 15 - 90 lbf.ft | 20 - 120 N.m | 5 lbf.ft | 5 N.m |
| DM 120-D | 110108 | Double | 15 - 90 lbf.ft | 20 - 120 N.m | 5 lbf.ft | 5 N.m |
| DM 200 | 110110 | Single | 30 - 150 lbf.ft | 40 - 200 N.m | 5 lbf.ft | 5 N.m |
| DM 200-D | 110114 | Double | 30 - 150 lbf.ft | 40 - 200 N.m | 5 lbf.ft | 5 N.m |
| DM 300 | 110104 | Single | 35 - 220 lbf.ft | 50 - 300 N.m | 5 lbf.ft | 5 N.m |
| DM 300-D | 110113 | Double | 35 - 220 lbf.ft | 50 - 300 N.m | 5 lbf.ft | 5 N.m |
| DM 360 | 110127 | Single | 60 - 260 lbf.ft | 80 - 360 N.m | 5 lbf.ft | 5 N.m |
| DM 360-D | 110129 | Double | 60 - 260 lbf.ft | 80 - 360 N.m | 5 lbf.ft | 5 N.m |
| DM 550 | 110130 | Single | 80 - 405 lbf.ft | 110 - 550 N.m | 10 lbf.ft | 10 N.m |
| DM 550-D | 110135 | Double | 80 - 405 lbf.ft | 110 - 550 N.m | 10 lbf.ft | 10 N.m |
| DM 760 | 110105 | Single | 105 - 560 lbf.ft | 140 - 760 N.m | 10 lbf.ft | 10 N.m |
| DM 760-D | 110136 | Double | 105 - 560 lbf.ft | 140 - 760 N.m | 10 lbf.ft | 10 N.m |
| DM 1000 | 110106 | Single | 380 - 730 lbf.ft | 520 - 1000 N.m | 10 lbf.ft | 10 N.m |
| DM 1000-D | 110137 | Double | 380 - 730 lbf.ft | 520 - 1000 N.m | 10 lbf.ft | 10 N.m |
| DM 2000 | 110107 | Single | 553 - 1475 lbf.ft | 750 - 2000 N.m | * | 50 N.m |
| DM 2000-D | 110138 | Double | 553 - 1475 lbf.ft | 750 - 2000 N.m | * | 50 N.m |
| DM 3000 | 110150 | Single | 1106 - 2212 lbf.ft | 1500 - 3000 N.m | * | 50 N.m |

* DM2000 & DM 3000 models are only available as a single scale model - N.m



RATCHET ADAPTER

Enables controlled tightening in combination with DM Series wrenches.
SEE PAGE 04.22

| Model | Square Drive | Length | | Weight | |
|-----------|--------------|-----------|---------|--------|------|
| | | in. | mm | lbs. | kg. |
| DM 12 | 1/4" | 7 1/4 | 185 | 0.6 | 0.24 |
| DM 30 | 1/4" | 10 1/2 | 265 | 1.3 | 0.58 |
| DM 30-D | 1/4" | 10 1/2 | 265 | 1.3 | 0.58 |
| DM 40 | 3/8" | 13 3/8 | 340 | 2.2 | 1 |
| DM 40-D | 3/8" | 13 3/8 | 340 | 2.2 | 1 |
| DM 120 | 1/2" | 18 1/4 | 463 | 3.3 | 1.5 |
| DM 120-D | 1/2" | 18 1/4 | 463 | 3.3 | 1.5 |
| DM 200 | 1/2" | 21 3/4 | 553 | 3.1 | 1.4 |
| DM 200-D | 1/2" | 21 3/4 | 553 | 3.1 | 1.4 |
| DM 300 | 1/2" | 24 1/3 | 618 | 4.4 | 2 |
| DM 300-D | 1/2" | 24 1/3 | 618 | 4.4 | 2 |
| DM 360 | 3/4" | 28 1/4 | 718 | 5.3 | 2.4 |
| DM 360-D | 3/4" | 28 1/4 | 718 | 5.3 | 2.4 |
| DM 550 | 3/4" | 32 | 812 | 6.4 | 2.9 |
| DM 550-D | 3/4" | 32 | 812 | 6.4 | 2.9 |
| DM 760 | 3/4" | 32 | 812 | 7.1 | 3.2 |
| DM 760-D | 3/4" | 32 | 812 | 7.1 | 3.2 |
| DM 1000 | 3/4" | *55 1/8 + | *1400 + | 12.4 | 5.6 |
| DM 1000-D | 3/4" | *55 1/8 + | *1400 + | 12.4 | 5.6 |
| DM 2000 | 1" | *78 2/3 + | *1988 + | 25.6 | 11.6 |
| DM 2000-D | 1" | *78 2/3 + | *1988 + | 25.6 | 11.6 |
| DM 3000 | 1 1/2" | *92 1/4 + | *2343 + | 29.1 | 13.2 |

* Models come with an extension tube.

KEY FEATURES

Designed and manufactured to meet or exceed the accuracy and repeatability of ISO 6789:2003 (\pm 4% of setting).

Lightweight design crafted with high-strength aluminum alloy. Full-metal construction.

Non-length dependent.

Ergonomically designed handgrip enables simple and safe operations.

Adjustable torque wrench available with single or double square drive.


Single square drive for controlled clockwise tightening.

Double square drive for controlled bi-directional tightening.

Setting of the torque by non-losable hexagon key in the handgrip. The smooth-running mechanism enables the setting to be made quickly without significant force needing to be applied.

Easy-to-read dual scale (American & S.I.) with a graduation scale. Except DM 2000 & 3000 models - N.m scale only.

Positive "click" can be heard and felt when torque is reached.



Setting the torque by non-losable hexagon key in the handgrip. The smooth-running mechanism enables the setting to be made quickly without significant force.



NOTE!

After being used, torque click wrenches should be turned back to the minimum scale value. This helps to preserve the springs and ensures a longer product life cycle with high precision.