



September 2006

www.ETorque.com



EDTW

Electronic Dial Torque Wrench



Accuracy +/- 1% of reading, +/- 1 digit.

Designed for R&D, QC, a lab or production environment.

Program pre-set torque.

Display rotates - LCD can be read from any side.

Three units of torque measurement available: N.m, lbf.ft, lbf.in

Selection of two operating modes: Track and Peak.

Non-length dependent.

Go/No Go LED's and a buzzer can be set for a high or low torque limits.

Four-digit display.

Battery operation.

Display rotates both ways (up to 359 degrees)

Model	Item #	Torque Ranges		Length		Sq. Drive	Weight	
		American	S.I.	in.	mm		lbs.	kg.
EDTW75i	290100	7.5 - 75 lbf.in	0.8 - 8.5 N.m	10.6	270	1/4	1.6	0.73
EDTW100i	290101	10 - 100 lbf.in	1.1 - 11.3 N.m	10.6	270	1/4	1.6	0.73
EDTW250i	290102	25 - 250 lbf.in	2.8 - 28.2 N.m	10.6	270	3/8	1.6	0.73
EDTW50F	290103	5 - 50 lbf.ft	6.8 - 67.8 N.m	10.6	270	3/8	1.6	0.73
EDTW250F	290104	25 - 250 lbf.ft	33.9 - 339 N.m	22	560	1/2	3	1.4
EDTW600F	290105	60 - 600 lbf.ft	81.3 - 813.5 N.m	47	1193.8	3/4	10	4.5



NOTE!

Uses standard 9v battery