



TBIH

Break-Over Wrench Interchangeable Head Style

KEY FEATURES

Designed and manufactured to meet or exceed the accuracy and repeatability requirements of ISO 6789:2003 ($\pm 6\%$ of setting).

"Breaks-over" when preset torque is reached eliminating overtorquing.

The break-over mechanism minimizes shock to assemblies.

Tamper-proof internal adjustment. No external adjustment scale - must be preset using a torque analyzer.

Torque ranges 25 ozf.in - 50 lbf.in. For smaller torque ranges see MMTB models.

Six different colored aluminum handles allow for color coding of specific torque values in production areas.

Small and lightweight. Ideal for use in restricted spaces.
Handle size: 5 1/2" L x 9/16" Dia.

Interchangeable heads are manufactured with a common center line so the torque setting remains the same when head sizes are changed.

TBIH also accepts Utica® "A" size heads.

Handle Color

| Item # | Item # | Item # | Item # | Item # | Item # | Torque Ranges |
|----------|----------|----------|----------|----------|----------|----------------|
| 068000-A | 068001-A | 068002-A | 068003-A | 068004-A | 067999-A | 25 - 50 ozf.in |
| 068000-B | 068001-B | 068002-B | 068003-B | 068004-B | 067999-B | 3 - 12 lbf.in |
| 068000-C | 068001-C | 068002-C | 068003-C | 068004-C | 067999-C | 12 - 21 lbf.in |
| 068000-D | 068001-D | 068002-D | 068003-D | 068004-D | 067999-D | 20 - 50 lbf.in |

NOTE!

Torque is easily adjusted by removing the cap and turning the adjustment screw with the 3/16" Hex Key (supplied). Then verify torque output using a torque analyzer.